



Effective August 16, 2004

Re: “Velacarb” FRP Installation Addendum

Manufacturer’s Updated Installation Procedures for Velacarb and Velaglass
FRP composite strengthening systems

Licensed Vela Systems Installer,

This letter is to inform you and your clients that the manufacturer of our FRP composite system, Edge Structural Composites, supplied under the Velacarb or Velaglass brand names, has updated their installation methods as follows.

Effective immediately, the priming of the surface to be wrapped should be performed using our standard Veloxx LR-A&B (laminating resin) product only. This procedure will be accomplished in the same manner as in the past using the Veloxx LVP-A&B (priming resin). Simply roll apply the LR-A&B resin and if necessary use a plastic screed to insure proper penetration into the concrete pores. Continue monitoring the primed surface for approximately 10 minutes, reapplying when and if dulling or dry areas in the primed surface develop. It will only be necessary to use the Veloxx LVP-A&B priming resin on red masonry brick or as otherwise directed by the manufacturer.

This modification has been developed for ease in installation of over-head or vertical wrap applications as well a superior fabric to structure cured bond in all applications. All other required steps in cleaning and preparing surfaces for our composite wrap systems remain in effect.

Kind Regards

Larry D. Durain
Sales Manager Specialty Products Division
The D.S. Brown Company