

MSDS Cableguard™ Wrap



The D.S. Brown Company
300 East Cherry Street
North Baltimore, OH 45872
419.257.3561
Fax: 419.257.2200
e-mail: dsb@dsbrown.com
www.dsbrown.com



1. Identification of the substance and company

Preparation/Product Name: Cableguard™
(Chlorosulfonated Polyethylene)

Product Code: NA

Intended Use: Corrosion Protection for Bridge Cables

Application Method: Consult Product Installation Manual

Company Name: The D. S. Brown Company
300 E. Cherry Street
North Baltimore, OH 45872

Telephone Number (419) 257-3561

24 hour Emergency Telephone No.: NA

2. Composition/information on ingredients

This product contains the following substances that present a health hazard within the meaning of the Dangerous Substances Directive 67/548/EEC and the Chemicals (Hazard Information and Packaging for Supply) Regulations SI/3247/1994 or have occupational exposure limits detailed in EH40.

Ingredient	CAS Number	Concentration	Label Symbol(s)	Risk Phrases(*)
No Hazardous Ingredients				

3. Hazards identification

No hazards identified.

4. First aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation

NA

Eye Contact

NA

Skin Contact

Wash any affected area.

Ingestion

NA

5. Fire-fighting measures

Recommended extinguishing media: Water, Fog, Foam, CO², Dry Chemical

Unusual Fire and Explosion Hazards: Combusts only with difficulty, HCl is decomposition and combustion product.

Special Fire-Fighting Procedures: Use approved self-contained breathing apparatus as appropriate.

6. Accidental release measures

Pick up material to avoid slipping/walking hazard.

Dispose per appropriate regulations.

Take personal protective measures listed in section 8.

7. Handling and storage**Handling**

NA

Storage

Store away from heat.

Use

Use personal protective equipment as outlined in section 8.

8. Exposure controls and personal protection**Engineering Measures**

Use local exhaust ventilation if needed.

Exposure Limits

The following occupational exposure limits have been established by the Health and Safety Executive as published in EH40.

Material	Short term (15 min. avg)		Long term (8hr time weighted avg)	
	ppm	mg/m ³	ppm	mg/m ³
NA				

Personal Protection**Respiratory Protection**

NA

Eye Protection

Wear safety eyewear, e.g. safety spectacles. Eyewear should comply with British Standard 2092.

Hand Protection

Recommended

Skin Protection

NA

Wash hands and face prior to eating, drinking or smoking.

9. Physical and chemical properties

Physical State:	Solid; hypalon sheeting with reinforced fabric
Odor:	NA
Flash Point (deg C):	NA
Viscosity (cSt):	NA
Specific Gravity:	1.314
Vapor Density:	NA
Lower Explosive Limit:	NA
Solubility in Water:	Negligible
R.A.Q. to ventilate to 10% of LEL (m³/l):	NA
pH:	NA

10. Stability and reactivity

Stable. Avoid sustained temperatures of 65.5° C (150° F) or above. Hazardous decomposition products include CO, HCl, SO₂ and other normal combustion product.

11. Toxicological information

Medical conditions aggravated by exposure: Sensitive skin may become itchy.

12. Ecological information

There are no data available on this product.

13. Disposal considerations

Wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

14. Transport information

NA

15. Regulatory Information

In accordance with EC Directive 88/379/EEC and the Chemicals (Hazard Information and Packaging for Supply) Regulations SI/3247/1994 this product is labeled as follows:

Symbol(s) NA

Contains: NA

R. Phrases: NA

S. Phrases: NA

P. Phrases: NA



Safety Data Sheet
*Cableguard*TM

Last Revised: 01/01/2002

*Cableguard*TM

16. Other information

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the user's responsibility to determine for itself the suitability of any material for a specific purpose, whether alone or in combination with any other products, and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions and methods of use are not under our control, we must necessarily disclaim all warranties of merchantability or fitness for any particular use as well as all liability resulting directly from the use of any material supplied by us. Nothing herein is to be considered as recommending any practice or any product in violation of any patent or in violation of any law or regulation.