


Section 1. Identification

GHS Product Identifier	: Deckguard Membrane, Part A
Other Means of Identification	: Not available.
Product Type	: Liquid
Product Use	: Component of a Polyurethane System
Supplier	: The D.S. Brown Company 300 East Cherry Street North Baltimore, Ohio 45872
In Case of Emergency	: Chemtrec 1-800-262-8200 International 01-703-741-5500

Section 2. Hazards Identification

OSHA/HCS Status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the Substance or Mixture	: Acute Toxicity: Inhalation - Category 4 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2B Respiratory Sensitization - Category 1 Skin Sensitization- Category 1 Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] - Category 3
Hazard Pictograms	: 
Signal Word	: Danger
Hazard Pictograms	: Harmful if inhaled. Causes skin and eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary Statements	: Wear protective gloves. Wear eye or face protection. In case of inadequate ventilation wear respiratory protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or physician if you feel unwell. If experiencing respiratory symptoms: Call a Poison Center or physician. If on Skin: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. If in Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other Hazards Which Do Not Result in Classification	: Not available.

Section 3. Composition/Information on Ingredients

Substance/Mixture : Mixture

Ingredient Name	CAS No.	%
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	53862-89-8	60-100
Diphenylmethane 4,4'-diisocyanate	101-68-8	30 - 60
Diphenylmethane-2,4'- diisocyanate	5873-54-1	13 - 30
Isocyanic acid, polymethylenepolyphenylene ester	9016-87-9	1 - 3

**The above components are hazardous as defined in 29 CFR 1910.1200*

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

- Eye Contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is laboured, oxygen should be administered by qualified personnel.
- Skin Contact** : After contact with skin, wash immediately with plenty of warm soapy water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

POTENTIAL ACUTE HEALTH EFFECTS

- Eye Contact** : Causes eye irritation.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. LC50 (rat) : ca. 490 mg/m³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.

Section 4. First Aid Measures *cont'd.*

POTENTIAL ACUTE HEALTH EFFECTS *cont'd.*

- Skin Contact** : Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.
- Ingestion** : Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

OVER-EXPOSURE SIGNS/SYMPTOMS

- Eye Contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
wheezing and breathing difficulties
asthma
- Skin Contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

- Notes to Physician** : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.
- Protection of First-Aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See Toxicological Information (Section 11)

Section 5. Fire-Fighting Measures

Flashpoint (method used) : Closed cup: >110°C (>230°F) [Setaflash.]

EXTINGUISHING MEDIA

Suitable Extinguishing Media : Foam, CO2 or dry powder.

Unsuitable Extinguishing Media : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous. Prevent washings from entering water courses, keep fire exposed containers cool by spraying with water.

Specific Hazards Arising From the Chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazard Thermal Decomposition Products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN.

Special Protective Actions for Fire-Fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special Protective Equipment for Fire-Fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

Section 6. Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For Non-Emergency Personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation inadequate. Put on appropriate personal protective equipment (see Section 8).

For Emergency Responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental Precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Materials for Containment and Cleaning Up : If the product is in its solid form: Spilled MDI flakes should be picked up carefully. The area should be vacuum cleaned to remove remaining dust particles completely. If the product is in its liquid form: Absorb spillages onto sand, earth or any suitable absorbent material. Leave to react for at least 30 minutes. Shovel into open-top drums for further decontamination. Wash the spillage area with water. Test atmosphere for MDI vapour. Neutralise small spillages with decontaminant. Remove and dispose of residues. The compositions of liquid decontaminants are given in Section 16. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING

- Protective Measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.
- Advice on General Occupational Hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

CONDITIONS FOR SAFE STORAGE

- Information for Safe Storage, Including Any Incompatibilities** : Store in accordance with local regulations. Keep container tightly closed in a cool, well-ventilated place. Keep away from moisture. Due to reaction with water producing CO₂-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Do not reseal contaminated containers. Uncontaminated containers, free of moisture, may be resealed only after placing under a nitrogen blanket. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.

Section 8. Exposure Controls/Personal Protection

CONTROL PARAMETERS

Occupational Exposure Limits

Ingredient Name	Exposure Limits
Diphenylmethane 4,4'-diisocyanate	<p>ACGIH TLV (United States, 3/2012). TWA: 0.005 ppm 8 hours.</p> <p>OSHA PEL (United States, 6/2010). CEIL: 0.02 ppm CEIL: 0.2 mg/m³</p>
Appropriate Engineering Controls	<p>: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Diisocyanates can only be smelled if the occupational exposure limit has been exceeded considerably.</p> <p>Medical supervision of all employees who handle or come in contact with respiratory sensitizers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products. The Occupational Exposure Limits listed do not apply to previously sensitized individuals. Sensitized individuals should be removed from any further exposure.</p>

Section 8. Exposure Controls/Personal Protection *cont'd.*

Environmental Exposure Controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

INDIVIDUAL PROTECTION MEASURES

Hygiene Measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Hand Protection : Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include :Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

Contaminated gloves should be decontaminated and disposed of.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/ specifications provided by the glove supplier. Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Body Protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek-Pro 'F' disposable coverall.

Other Skin Protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Thermal Hazards : Not available.

Section 9. Physical and Chemical Properties

Appearance	
Physical State	: Liquid
Color	: Not available.
Odor	: Not available.
Odor Threshold	: Not available.
pH	: Not available.
Melting Point/Freezing Point	: Not available.
Boiling/Condensation Point	: >300°C decomposes
Flash Point	: Closed cup: >110°C (>230°F) [Setaflash.]
Evaporation Rate	: Not available.
Flammability (Solid,Gas)	: Not available.
Lower and Upper Explosive (Flammable) Limits	: Not available.
Vapor Pressure	: Not available.
Vapor Density	: Not available.
Relative Density	: Not available.
Solubility in Water (%)	: Not available.
Partition Coefficient: n-octanol/water	: Not available.
Auto-Ignition Temperature	: >600°C
Decomposition Temperature	: Not available.
Viscosity	: Not available.

Section 10. Stability and Reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical Stability	: Stable at room temperature.
Possibility of Hazardous Reactions	: Reaction with water (moisture) produces CO ₂ -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.
Conditions to Avoid	: Avoid high temperatures.
Incompatible Materials	: Water, alcohols, amines, bases, and acids.
Hazardous Decomposition Products	: Combustion products may include: carbon oxides (CO, CO ₂) nitrogen oxides (NO, NO ₂ etc.) hydrocarbons and HCN.

Section 11. Toxicological Information

INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity

Product/Ingredient Name	Test	Endpoint	Species	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	-	LC50 Inhalation Dusts and Mists	Rat	0.49 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit-Male, Female	>9400 mg/kg
	No official guidelines	LD50 Intraperitoneal	Rabbit-Male	100 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat-Male	100 mg/kg
Diphenylmethane 4,4'-diisocyanate	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and Mists	Rat-Male Female	0.49 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit-Male	>9400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat-Male	>10000 mg/kg
Diphenylmethane-2,4'-diisocyanate	-	LC50 Inhalation Dusts and Mists	Rat	0.49 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit-Male, Female	>9400 mg/kg
	No official guidelines	LD50 Intraperitoneal	Rabbit-Male	100 mg/kg
Isocyanic acid, polymethylenepolyphenylene ester	OECD 403 Acute	LC50 Inhalation Dusts and Mists	Rat-Male,	0.49 mg/m ³
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Male, Female	>9400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat-Male	>10000 mg/kg

Conclusion/Summary : Diphenylmethane 4,4'- diisocyanate Irritating to respiratory system.

Irritation/Corrosion

Product/Ingredient Name	Test	Species	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes-Non-irritant
Diphenylmethane-4,4'-diisocyanate	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes-Non-irritant
Diphenylmethane-2,4'-diisocyanate	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes-Non-irritant
Isocyanic acid, polymethylenepolyphenylene ester	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Mild irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes-Non-irritant

Conclusion/Summary

Skin : isocyanates, reaction product of polyol with methylenediphenyl diisocyanate Irritating to the skin.

Eyes : isocyanates, reaction product of polyol with methylenediphenyl diisocyanate Based on the human occupational exposure data, this substance is considered as irritating to eyes.

Diphenylmethane-4,4'-diisocyanate Based on the human occupational exposure data, this substance is considered as irritating to eyes.

Section 11. Toxicological Information *cont'd.*

Irritation/Corrosion *cont'd.*

Conclusion/Summary *cont'd.*

Eyes <i>cont'd.</i>	: Diphenylmethane-2,4'-diisocyanate	Based on the human occupational exposure data, this substance is considered as irritating to eyes.
	Isocyanic acid, polymethylenepolyphenylene ester	Based on the human occupational exposure data, this substance is considered as irritating to eyes.
Respiratory	: isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	No additional information.
	Diphenylmethane-4,4'-diisocyanate	No additional information.
	Diphenylmethane-2,4'-diisocyanate	No additional information.
	Isocyanic acid, polymethylenepolyphenylene ester	No additional information.

Sensitization

Product/Ingredient Name	Test	Route of Exposure	Species	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	- No official guidelines	Skin Respiratory	Mouse Guinea Pig	Sensitizing Sensitizing
Diphenylmethane-4,4'-diisocyanate	OECD 429 Skin Sensitization: Local Lymph Node Assay OECD 406 Skin Sensitization No Official Guidelines	Skin Skin Respiratory	Mouse Guinea Pig Guinea Pig	Sensitizing Not Sensitizing Sensitizing
Diphenylmethane-2,4'-diisocyanate	- No Official Guidelines OECD 406 Skin Sensitization	Skin Respiratory Skin	Mouse Guinea Pig Guinea Pig	Sensitizing Sensitizing Not Sensitizing
Isocyanic acid, polymethylenepolyphenylene ester	No Official Guidelines -	Respiratory Skin	Rat Guinea Pig	Sensitizing Sensitizing

Mutagenicity

Product/Ingredient Name	Test	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic Activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Diphenylmethane-4,4'-diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic Activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Diphenylmethane-2,4'-diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic Activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative

Section 11. Toxicological Information *cont'd.*

Mutagenicity *cont'd.*

Product/Ingredient Name	Test	Result
Diphenylmethane-2,4'-diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic Activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Isocyanic acid, polymethylenepolyphenylene ester	Experiment: In vitro Subject: Bacteria Metabolic Activation: +/-	Negative
	Experiment: In vivo	Negative

Conclusion/Summary : Diphenylmethane-2,4'-diisocyanate No mutagenic effect.
Isocyanic acid, No mutagenic effect.
polymethylenepolyphenylene ester

Carcinogenicity

Product/Ingredient Name	Test	Species	Dose	Exposure	Result/Result Type
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	OECD 453 Acute Combined Chronic Toxicity/Carcinogenicity Studies	Rat-Male, Female	1 mg/m ³ l	2 years; 5 days per week	Positive-Inhalation-NOAEL
Diphenylmethane 4,4'-diisocyanate	OECD 453 Acute Combined Chronic Toxicity/Carcinogenicity Studies	Rat-Male, Female	1 mg/m ³ l	2 years; 5 days per week	Positive-Inhalation-NOAEL
Diphenylmethane-2,4'-diisocyanate	OECD 453 Acute Combined Chronic Toxicity/Carcinogenicity Studies	Rat-Male, Female	1 mg/m ³ l	2 years; 5 days per week	Negative-Inhalation-NOAEL
Isocyanic acid, polymethylenepolyphenylene ester	OECD 453 Acute Combined Chronic Toxicity/Carcinogenicity Studies EU	Rat-Female	0.7 mg/m ³ l	2 years; 5 days per week	Negative-Inhalation-NOAEL

Carcinogenicity Class

Product/Ingredient Name	IARC	OSHA
Diphenylmethane-2,4'-diisocyanate	3	-
Isocyanic acid, polymethylenepolyphenylene ester	3	-

Section 11. Toxicological Information *cont'd.*

Reproductive Toxicity

Ingredient Name	Test	Maternal Species	Toxicity	Fertility	Developmental Effects
Diphenylmethane-2,4'-diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat-Female	Negative	-	-
	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative	-	-
	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative	Negative	Negative
Isocyanic acid, polymethylenepolyphenylene ester	OECD 414 Prenatal Prenatal	Rat-Male, Female	Negative	Negative	Negative

Conclusion/Summary : Diphenylmethane 4,4' diisocyanate No known significant effects or critical hazards.

Isocyanic acid, polymethylene-phenylene ester No known significant effects or critical hazards.

Teratogenicity

Product/Ingredient Name	Test	Species	Result/Result Type
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative-Inhalation
Diphenylmethane-4,4'-diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat-Female	Negative-Inhalation
Diphenylmethane-2,4'-diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative-Inhalation
Isocyanic acid, polymethylenepolyphenylene ester	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative-Inhalation
	OECD 414 Prenatal Developmental Toxicity Study	Rat-Male, Female	Negative-Inhalation

Conclusion/Summary : Diphenylmethane 4,4' diisocyanate No known significant effects or critical hazards.

Isocyanic acid, polymethylene-phenylene ester No known significant effects or critical hazards.

Specific Target Organ Toxicity (Single Exposure)

Product/Ingredient Name	Category	Route of Exposure	Target Organs
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	Category 3	Not applicable.	Respiratory Tract Irritation
Diphenylmethane-4,4'-diisocyanate	Category 3	Not applicable.	Respiratory Tract Irritation
Diphenylmethane-2,4'-diisocyanate	Category 3	Not applicable.	Respiratory Tract Irritation
Isocyanic acid, polymethylenepolyphenylene ester	Category 3	Not applicable.	Respiratory Tract Irritation

Section 11. Toxicological Information *cont'd.*

Specific Target Organ Toxicity (Repeated Exposure) : Not available.

Aspiration Hazard : Not available.

Information on the Likely Routes of Exposure : Not available.

POTENTIAL ACUTE HEALTH EFFECTS

Eye Contact : Causes eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapor or aerosol at levels above the occupational exposure limit could cause respiratory sensitization.

Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized persons. LC50 (rat) : ca. 490 mg/m³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter < 5microns.

Skin Contact : Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitization can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

Ingestion : Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

Eye Contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
wheezing and breathing difficulties
asthma

Skin Contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Section 11. Toxicological Information *cont'd.*

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT- AND LONG-TERM EXPOSURE

Short-Term Exposure

Potential Immediate Effects : Not available.

Potential Delayed Effects : Not available.

Long-Term Exposure

Potential Immediate Effects : Not available.

Potential Delayed Effects : Not available.

Potential Chronic Health Effects

Product/Ingredient Name	Test	Endpoint	Species	Result
Isocyanic acid, polymethylenepolyphenylene ester	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	Chronic NOEC	Rat-Male, Female	0.2 mg/m ³

General : May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m³), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumors at 1 mg/m³ and no effects at 0.2 mg/m³. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumors were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumor formation will occur.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental Effects : No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.

Fertility Effects : No known significant effects or critical hazards.

Section 11. Toxicological Information *cont'd.*

Acute Toxicity Estimates

Route	ATE Value
Inhalation (dusts and mists)	1.5 mg/l
Other Information	: Not available.

Section 12. Ecological Information

Toxicity

Product/Ingredient Name	Test	Endpoint	Exposure	Species	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 Hours Static	Bacteria	>100 mg/l
	OECD 202 Daphnia sp. Acute Immobilization Test	Acute EC50	24 Hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish Acute Toxicity Test	Acute LC50	96 Hours Static	Fish	>1000 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 Days Semi-Static	Daphnia	>10 mg/l
Diphenylmethane-4,4'-diisocyanate	OECD 202 Daphnia sp. Acute Immobilization Test	Acute EC50	24 Hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish Acute Toxicity Test	Acute LC50	96 Hours Static	Fish	>1000 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 Days Semi-Static	Daphnia	>10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 Hours Static	Algae	>1640 mg/l
Diphenylmethane-2,4'-diisocyanate	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 Hours Static	Bacteria	>100 mg/l
	OECD 202 Daphnia sp. Acute Immobilization Test	Acute EC50	24 Hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish Acute Toxicity Test	Acute LC50	96 Hours Static	Fish	>1000 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 Days Semi-Static	Daphnia	>10 mg/l
Isocyanic acid polymethylenepolyphenylene ester	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 Hours Static	Bacteria	>100 mg/l
	OECD 202 Daphnia sp. Acute Immobilization Test	Acute EC50	24 Hours Static	Daphnia	>1000 mg/l
	-	Acute LC0	96 Hours	Fish	>1000 mg/l
	OECD 203 Fish Acute Toxicity Test	Acute LC50	96 Hours Static	Fish	>1000 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic EC50	72 Hours Static	Algae	>1640 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 Days Semi-Static	Daphnia	>10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 Hours Static	Algae	1640 mg/l

Section 12. Ecological Information *cont'd.*

Persistence and Degradability

Product/Ingredient Name	Test	Period	Result
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 Days	0%
Diphenylmethane-4,4'-diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 Days	0%
Diphenylmethane-2,4'-diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 Days	0%
Isocyanic acid polymethylenepolyphenylene ester	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 Days	0%

Conclusion/Summary	: isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	Not biodegradable.
	Diphenylmethane 4,4'-diisocyanate	Not biodegradable.
	Isocyanic acid, polymethylenepolyphenylene ester	Not biodegradable.

Product/Ingredient Name	Test	Species	Dose
Product/Ingredient Name	Aquatic Half-Life	Photolysis	Biodegradability
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	-	-	Not readily.
Diphenylmethane-4,4'-diisocyanate	Fresh Water 0.83 days	-	Not readily.
Diphenylmethane-2,4'-diisocyanate	-	-	Not readily.
Isocyanic acid polymethylenepolyphenylene ester	Fresh Water 0.83 days Modified MITI Test (II)	-	Not readily.

Bioaccumulative Potential

Product/Ingredient Name	LogPow	BCF	Potential
isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	4.51	200	Low
Diphenylmethane-4,4'-diisocyanate	4.51	200	Low
Diphenylmethane-2,4'-diisocyanate	4.51	200	Low
Isocyanic acid polymethylenepolyphenylene ester	-	200	Low

Section 12. Ecological Information *cont'd.*

Mobility in Soil	: By considering the production and use of the substance, it is unlikely that significant environmental exposure in the air or water will arise. Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino-diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relatively rapid OH radical attack, by calculation and by analogy with related diisocyanates.
Other Adverse Effects	: No known significant effects or critical hazards.
Other Ecological Information	
BOD5	: Not determined.
COD	: Not determined.
TOC	: Not determined.

Section 13. Disposal Considerations

Disposal Method	: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------------	---


Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport Information

Proper Shipping Name

DOT	: Other regulated substances, liquid, N.O.S. (Methylene Diphenyl Diisocyanate)
TDG	: Not regulated.
IMDG	: Not regulated.
IATA	: Not regulated.

Section 14. Transport Information *cont'd.*

Regulatory Information	UN No.	Classes	PG*	Label	Additional Information
DOT Classification	NA3082	9	III		Reportable quantity 5000 lbs. (2270 kg) Single containers less than 5,000 lbs. are not regulated.
TDG Classification	Not regulated.	-	-	-	-
IMDG Classification	Not regulated.	-	-	-	-
IATA Classification	Not regulated.	-	-	-	-

*PG: Packing Group

Section 15. Regulatory Information

**SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT
UNITED STATES REGULATIONS**

- TSCA 8(b) Inventory** : All components are listed or exempted.
- TSCA 5(a)2 Final Significant New Use Rule (SNUR)** : No ingredients listed.
- TSCA 5(e) Substance Consent Order** : No ingredients listed.
- TSCA 12(b) Export Notification** : No ingredients listed.
- SARA 311/312** : Immediate (acute) health hazard.

	Product Name	Concentration %
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPS)	Diphenylmethane 4, 4'-diisocyanate	25.272-30.906
	Isocyanic acid, polymethylenepolyphenylene ester	2.0085-2.79
Clean Air Act - Ozone Depleting Substances (ODS)	: This product does not contain nor is it manufactured with ozone depleting substances.	

	Product Name	Concentration %
SARA 313 Form R - Reporting Requirements	Diphenylmethane 4, 4'-diisocyanate	25.272-30.906
	Diphenylmethane 4, 4'-diisocyanate	9.906 - 13.189
	Isocyanic acid, polymethylenepolyphenylene ester	2.0085-2.79



Bridge the World with Leading Infrastructure Solutions

Section 15. Regulatory Information *cont'd.*

	Ingredient Name	%	Section 304 CERCLA Hazardous Substance	CERCLA Reportable Quantity (Lbs)	Product Reportable Quantity (Lbs)
CERCLA Hazardous Substances	Diphenylmethane 4, 4' diisocyanate	28.27	Listed	5000	17687

STATE REGULATIONS

Pennsylvania - RTK : Diphenylmethane 4,4'-diisocyanate, Isocyanic acid, polymethylenepolyphenylene ester

California Prop 65 : **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

Product Name	Cancer	Reproductive
Popylene oxide	Yes	No

CANADIAN REGULATIONS

CEPA DSL : All components are listed or exempted.

WHMIS Classes : WHMIS Class D-2A: Material causing other toxic effects (Very toxic).
WHMIS Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

INTERNATIONAL REGULATIONS

Brazil : Classification System Used: Norma ABNT-NBR 14725-2:2012

International Lists : **Australia inventory (AICS):** Not determined.

China inventory (IECSC): Not determined.

Japan inventory: Not determined.

Korea inventory: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan inventory (CSNN): Not determine

Section 16. Other Information

Hazardous Material Information System (USA) : Health: *2
Flammability: 1
Physical Hazards: 1
Personal Protection

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Nation Fire Protection Association (USA) : Health: 2
Flammability: 1
Instability: 1
Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of Printing : 04/30/2015

Date of Issue : 04/30/2015

Date of Previous Issue : 01/08/2014

Version : 3

➤ **Indicates information that has changed from previously issued version.**

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : *- sodium carbonate : 5 - 10 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 2 : *- concentrated ammonia solution : 3 - 8 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Literature reference: PU 193-1 : 'MDI-Based Compositions : Hazards and Safe Handling Procedures.'

PU 181-15 : Recommended melting procedures for MDI-based isocyanates.

ISOPA Guidelines for safe Loading/Unloading, Transportation, Storage of TDI and MDI , Ref.03-96 PSC-0005-GUIDL.

SPI PMDI User Guidelines for the Chemical Protective Clothing Selection.

Section 16. Other Information *cont'd.*

References of methods used in the Physico-Chemical Properties section are reported in Annex V part A to Commission Directive 92/69/EEC of 31 July 1992 adapting to technical progress for the Seventeenth time Council Directive 67/548/EEC.

Notice to Reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.