

Section 1. Identification

Trade Name : Chemlock AP-134 - Delcrete®/
Delpatch Primer

Identified Uses : Primer for Adhesives

Effective Date : 03/13/2020

Supersedes Date : 10/31/2016

Supplier : The D.S. Brown Company
300 East Cherry Street
North Baltimore, Ohio 45872

In Case of Emergency : Chemtrec 1-800-424-9300
International 01-703-741-5500



[YouTube Video -
Delcrete Elastomeric
Concrete](#)



[DSB Installation Sheet
Delcrete-m \(5.6 CF\)*](#)



[DSB Installation Sheet
Delcrete with DelAgg
Elastomeric Concrete
System*](#)



[DSB Installation Sheet
Delcrete with Sand /
Fiberglass Aggregate
System*](#)



[YouTube Video -
Delpatch](#)



[DSB Installation Sheet
Delpatch Elastomeric
Concrete](#)

*Delcrete is available in various unit sizes that require different mixing ratios. Please refer to your actual Delcrete packaging to confirm which of these Delcrete installation instructions are applicable to your product.

Section 2. Hazards Identification

Classification of the

| | | |
|-----------------------------|---|--|
| Substance or Mixture | : Flammable liquids Acute toxicity Inhalation – dust and mist Acute toxicity Inhalation – vapors Skin corrosion/irritation Serious eye damage/eye irritation Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organ systemic toxicity (single exposure) | Category 2 Category 4 – 18.0% of the mixture consists of ingredient(s) of unknown toxicity. Category 4 – 18.0% of the mixture consists of ingredient(s) of unknown toxicity. Category 2 Category 1 Category 1B Category 1A Category 2 Category 3 |
|-----------------------------|---|--|



Bridge the World with Leading Infrastructure Solutions

Section 2. Hazards Identification *cont'd.*

| | |
|---|--|
| Specific target organ systemic toxicity (single exposure) | Category 1 |
| Specific target organ systemic toxicity (repeated exposure) | Category 2 – blood, nervous system |
| Specific target organ systemic toxicity (repeated exposure) | Category 1 – central nervous system, kidney, liver, ears |
| Aspiration hazard | Category 1 |
| Hazardous to the aquatic environment - acute hazard | Category 2 |
| Hazardous to the aquatic environment - chronic hazard | Category 2 |

Label Elements

GHS Label Elements

The product is classified and labeled according to the Globally Harmonized System



Signal Word

: **Danger**

Hazard Statements

: Highly flammable liquid and vapor.
 Harmful if inhaled.
 Causes skin irritation.
 Causes serious eye damage.
 May cause genetic defects.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 May cause harm to breast-fed children.
 May cause drowsiness or dizziness.
 May cause respiratory irritation.
 Causes damage to organs. (Central nervous system, blood, kidney, liver)
 May cause damage to organs through prolonged or repeated exposure. (Blood, nervous system)
 Causes damage to organs through prolonged or repeated exposure. (Central nervous system, kidney, liver, ears)
 May be fatal if swallowed and enters airways.
 Toxic to aquatic life.
 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/Bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Obtain special instructions before use.

Section 2. Hazards Identification *cont'd.*

Do not handle until all safety precautions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Use personal protective equipment as required.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Avoid release to the environment.

Response : In case of fire: refer to section 5 of SDS for extinguishing media.
 Immediately call a poison center or doctor/physician.
 Specific treatment (see supplemental first aid instructions on this label).
If inhaled: Remove to fresh air and keep at rest in a position comfortable for breathing.
If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Do NOT induce vomiting.
 Collect spillage.

Storage : Store in a well-ventilated place. Keep cool.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.

Disposal : Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute : Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. May be absorbed through the skin in harmful amounts. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause headache and nausea. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic : Prolonged or repeated contact may result in dermatitis. ACGIH considers Ethyl alcohol to be an A3 carcinogen (confirmed animal carcinogen with unknown relevance in humans).

Section 3. Composition/Information on Ingredients

| Chemical Name | CAS No. | Range |
|-----------------|----------|--------|
| Toluene | 108-88-3 | 70–75% |
| N-Butanol | 71-36-3 | 1–5% |
| 2-Butoxyethanol | 111-76-2 | 1–5% |
| Ethyl Alcohol | 64-17-5 | 1–5% |

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

Section 4. First Aid Measures

DESCRIPTION OF FIRST AID MEASURES

- After Eye Contact** : Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.
- After Skin Contact** : Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.
- After Inhalation** : Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.
- After Ingestion** : If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

DESCRIPTION OF INFORMATION FOR DOCTOR

- Most Important Symptoms/ Effects, Both Acute and Delayed** : No further relevant information available.
- Indication of Any Immediate Medical Attention and Special Treatment Needed** : No further relevant information available.

Section 5. Fire-Fighting Measures

EXTINGUISHING MEDIA

- Suitable Extinguishing Media** : Carbon Dioxide, Dry Chemical, Foam, Water Fog
- Specific Hazards Possibly Arising from the Chemical** : Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

ADVICE FOR FIREFIGHTERS

- Protective Equipment** : Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.



Bridge the World with Leading Infrastructure Solutions

Section 6. Accidental Release Measures

- Personal Precautions, Protective Equipment, and Emergency Procedures** : Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.
- Environmental Precautions** : Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.
- Methods and Materials for Containment and Cleanup** : Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material.

Section 7. Handling and Storage

HANDLING

- Precautions for Safe Handling** : Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Storage Requirements to be Met by Storerooms and Receptacles** : Do not store or use near heat, sparks or open flame. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Do not puncture, drag or slide container. Keep container closed when not in use.
- Incompatibility** : Strong acids, bases, and strong oxidizers.

Section 8. Exposure Controls/Personal Protection

Component Exposure Limit

| Chemical Name | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING | SKIN |
|-----------------|---------------|----------------|--------------------------|------------------|------|
| Toluene | 20 ppm | N.E. | 200 ppm | 300 ppm | N.A. |
| N-Butanol | 20 ppm | N.E. | 300 mg/m3 100 ppm | N.E. | S |
| 2-Butoxyethanol | 20 ppm | N.E. | 240 mg/m3 50 ppm | N.E. | S |
| Ethyl alcohol | N.E. | 1,000 ppm | 1,900 mg/m3 1,000 ppm | N.E. | N.A. |

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering Controls

: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

EXPOSURE CONTROLS

Personal Protection Measures/Equipment

Breathing Equipment

: Use a NIOSH/MSHA approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29 CFR 1910.134) for respirator use.

Protection of Hands

: Use neoprene, nitrile or rubber gloves to prevent skin contact.

Eye Protection

: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

Other Protective Equipment

: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Hygienic Practices

: Wash hands before eating, smoking or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

Section 9. Physical and Chemical Properties

Typical values, not to be used for specification purposes.

Appearance

| | |
|---|---------------------------------------|
| Form | : Liquid |
| Color | : Clear |
| Odor | : Solvent |
| Odor Threshold | : N.D. |
| pH Value | : N.A. |
| Physical State | : Liquid |
| Flash Point | : 1°C (35°F) Setaflash Closed Cup |
| Boiling Point Range | : 78–171°C |
| Auto Ignition Temperature | : N.D. |
| Decomposition Temperature | : N.D. |
| Solubility in H ₂ O | : Insoluble |
| Freeze Point | : 10.8 |
| Coefficient of Water/ Oil Distribution | : N.D. |
| Vapor Pressure | : N.D. |
| Explosion Limits | |
| Lower | : 1.1%(V) |
| Upper | : 19%(V) |
| Density at 20°C (68°F) | : 0.9 g/cm ³ - 7.47 lb/gal |
| Vapor Density | : Heavier than air |
| Evaporation Rate | : Slower than n-butylacetate |
| Viscosity | |
| Dynamic | : ≥0.9 mPa.s @ 25°C |
| Kinematic | : ≥1 mm ² /s @ 25°C |
| Volatile by Weight | : 87.09% |
| Volatile by Volume | : 90.37% |
| VOC Calculated | : 6.5 lb/gal, 779 g/l |
| Method 24 | : 6.87 lb/gallon |

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Section 10. Stability and Reactivity

| | |
|-------------------------------------|--|
| Hazardous Polymerization | : Hazardous polymerization will not occur under normal conditions. |
| Stability | : Product is stable under normal storage conditions. |
| Conditions to Avoid | : High temperatures. Sources of ignition. |
| Incompatible Materials | : Strong acids, bases, and strong oxidizers. |
| Hazardous Decomposition Products | : Carbon monoxide, carbon dioxide. |



Bridge the World with Leading Infrastructure Solutions

Section 11. Toxicological Information

Exposure Path : Refer to section 2 of this SDS.

Symptoms : Refer to section 2 of this SDS.

Toxicity Measures

| Chemical Name | LD50/LC50 |
|-----------------|--|
| Toluene | Oral LD50: Rat 2,600 mg/kg Dermal LD50: Rabbit 12,000 mg/kg Inhalation LC50: Rat 12.5 mg/l /4 h |
| N-Butanol | Oral LD50: Rat 790 mg/kg Oral LD50: Rat 700 mg/kg Dermal LD50: Rabbit 3,400 mg/kg Dermal LD50: Rabbit 3,402 mg/kg Inhalation LC50: Rat >8000 ppm/4 h |
| 2-Butoxyethanol | Oral LD50: Rat 470 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l / GHS LC50 (dust and mist): Acute toxicity point estimate 1.5 mg/l / |
| Ethyl alcohol | Oral LD50: Rat 7,060 mg/kg Inhalation LC50: Rat 124.7 mg/l /4 h |

Germ cell mutagenicity : Category 1B - May cause genetic defects.
Components contributing to classification: Ethyl alcohol.

Carcinogenicity : Category 1A - May cause cancer.
Components contributing to classification: Ethyl alcohol.

Reproductive toxicity : Category 2 - Suspected of damaging fertility or the unborn child. May cause harm to breastfed children.
Components contributing to classification: Toluene. 2-Butoxyethanol. Ethyl alcohol. Methanol.

Section 12. Ecological Information

Ecotoxicity

| Chemical Name | Ecotoxicity |
|---------------|--|
| Toluene | Fish: Pimephales promelas 15.22 - 19.05 mg/l/96 h flow-through Pimephales promelas 12.6 mg/l/96 h Static Oncorhynchus mykiss 5.89 - 7.81 mg/l/96 h flow-through Oncorhynchus mykiss 14.1 - 17.16 mg/l/96 h Static Oncorhynchus mykiss 5.8 mg/l/96 h semi-static Lepomis macrochirus 11.0 - 15.0 mg/l/96 h Static Oryzias latipes 54 mg/l/96 h Static Poecilia reticulata 28.2 mg/l/96 h semi-static Poecilia reticulata 50.87 - 70.34 mg/l/96 h Static Invertebrates: Daphnia magna 5.46 - 9.83 mg/l/48 h Static Daphnia magna 11.5 mg/l/48 h Plants: Pseudokirchneriella subcapitata > 433 mg/l/96 h Pseudokirchneriella subcapitata 12.5 mg/l/72 h Static |
| N-Butanol | Fish: Pimephales promelas 1,730 - 1,910 mg/l/96 h Static Pimephales promelas 1,740 mg/l/96 h flow-through Lepomis macrochirus 100,000 - 500,000 µg/l/96 h Static Pimephales promelas 1,910,000 µg/l/96 h Static Invertebrates: Daphnia magna 1,983 mg/l/48 h Daphnia magna 1,897 - 2,072 mg/l/48 h Static Plants: Desmodemus subspicatus > 500 mg/l/96 h Desmodemus subspicatus > 500 mg/l/72 h |

Ecotoxicity (continued)

| Chemical Name | Ecotoxicity |
|-----------------|---|
| 2-Butoxyethanol | Fish: Lepomis macrochirus 1,490 mg/196 h Static Lepomis macrochirus 2,950 mg/196 h Invertebrates: Daphnia magna > 1,000 mg/148 h |
| Ethyl alcohol | Fish: Pimephales promelas > 100 mg/196 h Static Pimephales promelas 13,400 - 15,100 mg/196 h flow-through Invertebrates: Daphnia magna 9,268 - 14,221 mg/148 h Daphnia magna 2 mg/148 h Static |

TOXICITY

Persistence and Degradability : Not determined for this product.

BEHAVIOR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative Potential : Not determined for this product.

Mobility in Soil : Not determined for this product.

Other Adverse Effects : Not determined for this product.

Section 13. Disposal Considerations

Recommendation : Disposal should be done in accordance with federal (40 CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

Section 14. Transport Information

US DOT Road

DOT Proper Shipping Name : Adhesives
DOT Hazard Class : 3
Secondary Hazard : None
DOT UN/NA Number : 1133
Packing Group : II
Emergency Response Guide Number : 128

IATA Cargo

Proper Shipping Name : Adhesives
DOT Hazard Class : 3
Hazard Class : None
UN-Number : 1133
Packing Group : II
EMS : 3L

Section 14. Transport Information (continued)

IMDG

| | |
|-----------------------------|-------------|
| Proper Shipping Name | : Adhesives |
| DOT Hazard Class | : 3 |
| Hazard Class | : None |
| UN-Number | : 1133 |
| Packing Group | : II |
| EMS | : F-E |

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

Section 15. Regulatory Information

| | |
|---------------------------------|--|
| U.S. Federal Regulations | : As follows |
| SARA Section 313 | : This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372. |

| Chemical Name | CAS Number | Weight % Less Than |
|-----------------|------------|--------------------|
| Toluene | 108-88-3 | 75.0% |
| N-Butanol | 71-36-3 | 5.0% |
| 2-Butoxyethanol | 111-76-2 | 5.0% |

TSCA (Toxic Substances Control Act)

| | |
|----------------------------|--|
| Inventory Status | : The chemical substances in this product are on the TSCA Section 8 Inventory. |
| Export Notification | : This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: NONE |

Section 16. Other Information

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

| | |
|---------------------|--|
| HMIS Ratings | : Health = 2* Flammability = 3 Physical Hazard = 0 <i>*Indicates a chronic hazard; see Section 2.</i> |
|---------------------|--|

| | |
|-----------------------|----------------------|
| Revision | : New GHS SDS Format |
| Effective Date | : 3/13/2020 |

| | |
|-------------------|--|
| Disclaimer | : The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. |
|-------------------|--|



Bridge the World with Leading Infrastructure Solutions